TECHNICAL DATA SHEET: ACMOSAN P82-271

Range of application:

External Release Agent for UP/EP resins

Properties:

Dispersion of waxes in a mixture of solvents

Physical and chemical properties:

Form:	Paste	
Appearance:	white	
Smell:	characteristic	
Density at 20° C:	0,8 g/ml	**DIN 51757**
Active substances:	23,10	
Flashpoint:	> 24 °C	**Literaturhinweis**
Viscosity at 20° C:	> 90 sec	**Flow cup 4mm** **DIN EN ISO 2431**

Stockage:

Storage temperature: between 10° C and 30° C
Maximum storage: approx. 6 months

Processing:

Do not store outdoors. Protect from heat and cold.   Allow products to reach room temperature before use.

Bremen, 31.08.2012

All information of this data sheet correspond to the formula. The values mentioned are standard guidelines and have been ascertained or calculated by stated measuring methods. They do not replace any specification. Errors excepted. Additional information can be found in the ACMOS EU safety data sheet.

ACMOSAN P82-271

External Release Agent for UP/EP resins

Properties:

Paste Release Agent
The Release Agent is best suitable for epoxy resin concrete

Advantages:

Minimal cleaning stops
Economic in use

Processing:

The Release Agent should be at room temperature before processing.

For best results apply by paintbrush or cloth.

Before polishing the solvents have to be flashed off.

Before first coating is applied the mould should be cleaned with an ACMOSOL Mould Cleaner.

Storage:

Do not store outdoors. Protect from heat and cold.   Allow products to reach room temperature before use.
Storage temperature: between 10° C and 30° C
Maximum storage: approx. 6 months (originally sealed container)

Additional information can be found in the ACMOS EU safety data sheet.

Our Sales and Technical Department are always at your disposal to answer technical queries.

Bremen, 31.08.2012