



# MANDURAX

## MINERAL PRODUCT

### KEY BENEFITS

- Wear resistance
- Rust free
- Acid proof

### DESCRIPTION

Simson Mandurax is mineral product with a high toughness and hardness. After diamond, Mandurax is the hardest material that is found in nature.

### APPLICATION

Mandurax is used as an antiskid material for floor finishing of a Marothaan floor.

### FEATURES

- Wear-resistant; Mandurax is broken and sifted in such a way that hard and sharp grains exist, which ensure a maximum wear-resistance
- Rust-free; Mandurax doesn't even rust in the most unfavorable circumstances and keep its original color
- Antiskid; Because of the uneven planes of fracture of the grains, the Marothaan floor scattered with Mandurax has excellent antiskid properties
- Acid-proof; Mandurax has a good resistance against the influences of acids

### METHOD OF USE

Application process: Apply at a temperature between +15°C and +25°C at a relative humidity of 40% to 60%.

**Substrate:** Marothaan.

**Application:** Approximately 2 hours (at 20°C and 55% R.H.) after applying Marothaan, the floor can be scattered with Mandurax grains. After 3 to 4 hours the floor is cured sufficiently to walk on it and finish it with Simson Marotop 2316.

**Consumption:** Approx. 0,5 kg/m<sup>2</sup> (depending on the type of Mandurax and the desired antiskid properties).

### GRAIN SIZE

- Mandurax extra fine 0.7 – 1.2 mm
- Mandurax D113 1.0 – 2.0 mm

### PACKAGING

25 kg bag

### STORAGE

Store Mandurax in a cool and dry place at temperatures between +15°C and +25°C. Mandurax is kept well for an unrestricted time in its original, unopened packaging.

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

### SMART HELP

Please contact your local representative

